

Industrial M12 Managed Switches				
	<u>LMP-1600G-M12-67-24</u>	<u>LMP-1600G-M12-67-110</u>	<u>LMX-1600G-M12-67</u>	<u>LMX-1600G-M12-67-110</u>
Ethernet Port	16*1G	16*1G	16*1G	16*1G
Fiber Port Count	-	-	-	-
Input Voltage	24V–55V DC, Redundant Input	24V–110V DC, Redundant Input	12V–48V DC, Redundant Input	24V–110V DC, Redundant Input
Max. PoE Power Budget	Max. 240 Watts	Max. 120 Watts	-	-
Operating Temperature	STD: -10° to 65° C (14° to 149° F) EOT: -40° to 70° C (-40° to 158° F)	STD: -10° to 65° C (14° to 149° F) EOT: -40° to 70° C (-40° to 158° F)	STD: -10° to 65° C (14° to 149° F) EOT: -40° to 70° C (-40° to 158° F)	STD: -10° to 65° C (14° to 149° F) EOT: -40° to 70° C (-40° to 158° F)
Housing	Metal, IP67 protection	Metal, IP67 protection	Metal, IP67 protection	Metal, IP67 protection
Mounting	Wall mount	Wall mount	Wall mount	Wall mount
Dimensions (W × H × D)	160 × 295 × 100 mm	160 × 295 × 100 mm	160 × 295 × 100 mm	160 × 295 × 100 mm
EN50155	✓	✓	✓	✓
EN50121-4	✓	✓	✓	✓
Warranty	5 years	5 years	5 years	5 years