

PoE++ Injector



Model Name	INJ-C201G-bt-T	INJ-C201G-bt-24-T	INJ-C201G-bt-100-T	INJ-C201G-bt-100-24-T
	Learn More	Learn More	Learn More	Learn More
10/100/1000BaseT(X) Ports RJ45 Connector	1	1	1	1
PoE Ports, 10/100/1000BaseT(X) RJ45 Connector	1	1	1	1
Input Voltage	48V–55V DC, Redundant Input	9V–55V DC, Redundant Input	48V–55V DC, Redundant Input	9V–55V DC, Redundant Input
Max. PoE Power Budget	90 Watts	60W@9V, 90W@12-55V	100 Watts	60W@9V, 90W@12V, 100W@24-55V
Dual PD Failure Check			✓	✓
PoE Budget Control				✓
Operating Temperature	-40° to 75° C (-40° to 167° F)	-40° to 75° C (-40° to 167° F)	-40° to 75° C (-40° to 167° F)	-40° to 75° C (-40° to 167° F)
Housing	Metal, IP30 protection	Metal, IP30 protection	Metal, IP30 protection	Metal, IP30 protection
Mounting	DIN-Rail mount, Wall mount (Optional)	DIN-Rail mount, Wall mount (Optional)	DIN-Rail mount, Wall mount (Optional)	DIN-Rail mount, Wall mount (Optional)
Dimensions (W × H × D)	30 x 95 x 75 mm	30 x 95 x 75 mm	30 x 95 x 75 mm	30 x 95 x 75 mm
Warranty	5 years	5 years	5 years	5 years