

Ref. No.:	PhO-LNP-1002G
Date:	March 09, 2015

## PRODUCT NOTICE

Dear Valued Customers,

The purpose of this product notice is to inform you that the following Antaira product model will be phased out on March 09, 2015.

<b>Phase-Out Model Name:</b>	<b>LNP-1002G (T) Series</b>  10-Port Industrial PoE Unmanaged Ethernet Switch, w/8*10/100TX (15.4W/Port), + 2*GigE Combo Ports
<b>Alternative Model Name:</b>	<b>LNP-1002C-SFP (T) Series</b>  10-Port Industrial PoE+ Gigabit Unmanaged Ethernet Switch, w/8*10/100TX (w/30W/Port), + 2*GigE Combo Ports (2*10/100/1000Tx RJ45 and 2*100/1000 SFP Slots)

Below, is the full phase-out schedule and information for the LNP-1002G (T) series.

- **Phase-Out Notice:** March 09, 2015
- **Phase-Out Start Date:** March 09, 2015
- **Alternative Model Ship Date:** March 10, 2015



The new and alternative replacement version of the LNP-1002C-SFP(T) series is 100% compatible with the old version of the LNP-1002G(T) series. It is a 10-port unmanaged switch with 8\*10/100Tx Fast Ethernet ports that are upgraded with the latest IEEE 802.3at technology that provides a maximum PoE power function up to 30W per port. It will also support any powered device requiring 802.3af standard PoE. The two gigabit combo ports are also designed and developed with 2\*10/100/1000Tx RJ45 and 2\*100/1000 dual rate SFP slots for fiber connectivity solutions.

We appreciate your understanding and patience as we phase-out the LNP-1002G (T) series. If your project still requires the LNP-1002G (T) series, please contact the Antaira Sales Team at 714-671-9000 or [sales@antaira.com](mailto:sales@antaira.com) and we will initiate the appropriate action. Please note that all service rules (e.g., warranty) will still apply after this product is phased out.

Regards,

Antaira Technologies

## SPECIFICATIONS

	OLD VERSION	ALTERNATIVE VERSION
Pictures		
Model Names	<b>LNP-1002G (T) Series</b>	<b>LNP-1002C (T) Series</b>
Total Port Count	10	10
<b>SPECIFICATIONS</b>		
Technology Standard	IEEE 802.3, 802.3u, 802.3x, 802.3ab, 802.3z, 802.3af (PoE)	IEEE 802.3, 802.3u, 802.3x, 802.3ab, 802.3z, <b>802.3at/af (PoE+/PoE)</b>
<b>INTERFACE</b>		
Ethernet Port	8*10/100Tx (PSE: 15.4W/Port)	<b>8*10/100Tx (PSE: 30W/Port)</b>
PoE Pin Out	1,2 (V+), 3,6 (V-)	1,2 (V+), 3,6 (V-)
Gigabit Combo Port	2*10/100/100TxRJ45 + 2*/100/1000X SFP Slots	2*10/100/100TxRJ45 + 2*/100/1000X SFP Slots
<b>MECHANICAL CHARACTERISTICS</b>		
Dimensions	72 x 152 x 105 mm	<b>46 x 142 x 99 mm</b>
Weight	Unit: 2.5 lbs.; Shipping: 3.0 lbs.	<b>Unit: 1.5 lbs.; Shipping: 2.0 lbs.</b>
<b>ENVIRONMENTAL LIMITS</b>		
Operating Temperature	STD:-10°C to 70°C EOT:-40°C to 80°C	<b>STD:-10°C to 70°C EOT:-40°C to 75°C</b>
<b>REGULATORY APPROVALS</b>		
Certifications	CE, FCC, UL	<b>CE, FCC UL 508 (Pending)</b>