

Ref. No.:	PhO-LNX-800N
Date:	March 17, 2016

PRODUCT NOTICE

Dear Valued Customers,

The purpose of this product notice is to inform you that the following Antaira product model will be phased out on March 17, 2016.

Phase-Out Model Name:	LNX-800N Series 8-Port Industrial Managed Ethernet Switch w/ 8*10/100Tx Ports
Alternative Model Name:	LMX-0800 Series 8-Port Industrial Managed Ethernet Switch w/ 8*10/100Tx Ports

Below, is the full phase-out schedule and information for the LNX-800N series.

- **Phase-Out Start Date: March 17, 2016**
- **Phase-In Alternative Model Start Date: March 23, 2016**

This is an immediate phase out notice for Antaira's LNX-800N series. Due to new developments in the hardware of the device, as well as, limitations of the old components did not apply the latest network application requirements. Antaira will launch the alternative replacement model with the latest advanced technologies to support the market on March 23, 2016.



The new and advanced replacement, LMX-0800 series is an 8-port industrial managed Ethernet switch w/ 8*10/100Tx ports. This new series of the 8-port managed switch utilizes a stronger Ethernet chipset and is able to offer greater backplane speeds for stronger network communication.

We appreciate your understanding and patience as we phase-out the LNX-800N series and would highly recommend to our customers to utilize the benefits of the new advanced technology solution products. If your project still requires this discontinued product, please contact the Antaira Sales Team at 714-671-9000 or sales@antaira.com and they will initiate the appropriate action. Please note that all service rules (e.g., warranty) will still apply after this product is phased out.

Regards,

Antaira Technologies

SPECIFICATIONS

	OLD VERSION	NEW VERSION
Pictures		
Model Names	LNX-800N Series	LMX-0800 Series
Total Port Count	6	6
SPECIFICATIONS		
Technology Standard	IEEE 802.3, 802.3u, 802.3x, 802.1D, 802.1p, 802.1Q, 802.1w, 802.1s, 802.1x	IEEE 802.3, 802.3x, 802.3ad, 802.1D, 802.1p, 802.1Q, 802.1w, 802.1s, 802.1x
INTERFACE		
Ethernet Port	8*10/100Tx	8*10/100Tx
Serial Console	-	Present
Configuration Backup	-	1*USB2.0
Network Management & Control		
System Configuration	Web Console	Web Console or CLI
Network Redundancy	STP/RSTP	STP/RSTP/MSTP,ERPS G.8032 Open Standard
Protocols	IGMPv1/v2, SNMPv1/v2c/v3, TFTP,HTTPS,	IGMPv1/v2, SNMPv1/v2c/v3, TFTP, SMTP, RMON, HTTPS, Telnet, Syslog, DHCP Option 66/67/82, Modbus/TCP
Quality of Service	CoS / ToS	CoS / ToS
System Warning Email Alert	Present	Present
Power Requirement		
Power Input	12-48VDC	12-48VDC
Reverse Polarity Protection	Present	Present
Power Consumption	10 Watts for unit	15 Watts for unit
MECHANICAL CHARACTERISTICS		
Dimensions	54 x 135 x 105mm	54 x 142 x 99mm
Weight	Unit: 1.5 lbs. / Shipping 2.0 lbs.	Unit: 1.5 lbs. / Shipping 2.0 lbs.
Environmental Limits		
Operating Temperature	STD: -10 to 60C EOT: -40 to 70C	STD: -10 to 70C EOT: -40 to 75C
Protection	-	EFT 2,000 VDC ESD 6,000 VDC
Regulatory Approvals		
Certifications	CE, FCC, EN60068-2-27,6,32	FCC, CE, UL61010-2-201(Pending), EN60068-2-27,6,32 EN61000-4-3,4,5,6,8