

Ref. No.:	PhO-USB-HUB7K
Date:	September 6, 2016

PRODUCT NOTICE

Dear Valued Customers,

The purpose of this product notice is to inform you that the following Antaira product model will be phased out effective September 6, 2016.

Phase-Out Model Name:	USB-HUB7K Industrial 7-Port USB2.0 Hub, Metal Case with Locking Feature
Alternative Model Name:	USB-HUB7K-V2 Industrial 7-Port USB2.0 Hub, Metal Case with Locking Feature

Below, is the full phase-out schedule and information for the USB-HUB7K.

- **Phase-Out Notice:** September 6, 2016
- **Phase –Out Start Date:** September 6, 2016
- **Alternative Model Availability:** USB-HUB7K-V2

This immediate Phase Out Notice for Antaira’s **USB-HUB7K** is due to obsolescence and a limited availability of components. Antaira has already launched alternative replacement models with the latest advanced technologies. This new alternative version has already been put into production and is currently in stock and ready for purchase.



The **new alternative replacement version USB-HUB7K-V2** utilizes enhanced components within the industrial USB hub. The new version of the 7-port USB 2.0 hub utilizes a stronger NEC for data communication. The operation and housing of the unit will remain the same to allow for a seamless transition.

We appreciate your understanding and patience as we phase-out the USB-HUB3-7K series. It is highly recommended for customers to utilize the benefits of the new advanced technology solution products. If your project still requires this discontinued product, please contact the Antaira Sales Team at 714-671-9000 or sales@antaira.com and they will initiate the appropriate action. Please note that all service rules (e.g., warranty) will still apply after this product is phased out.

Regards,

Antaira Technologies

SPECIFICATIONS

	Phased-Out Model	Alternative Replacement Model
Pictures		
Model Names	USB-HUB7K	USB-HUB7K-V2
Total Port Count	7	7
SPECIFICATIONS		
Technology Standard	USB 1.1 and 2.0 communication	USB 1.1 and 2.0 communication
INTERFACE		
Input Ports	1*USB 2.0 Type-B Connectors	1*USB 2.0 Type-B Connectors
Output Ports	7*USB 2.0 Type-A Connectors	7*USB 2.0 Type-A Connectors
NETWORK MANAGEMENT & CONTROL		
Chip	Renesas UDP720113	Terminus FE2.1
Transaction Translators	1	4
Throughput	Max 480Mbps	Max 480Mbps
POWER REQUIREMENTS		
Power Input	7~40 VDC Power Input	7~40 VDC Power Input
Power Connection	1 Removable 2-Contact Terminal Block	1 Removable 2-Contact Terminal Block
Power Output	Max 900mA USB Bus Power	Max 900mA USB Bus Power
MECHANICAL CHARACTERISTICS		
LED	Power (Red)	Power (Red)
Dimensions	65 x 36 x 113 mm (H x W x D)	65 x 36 x 113 mm (H x W x D)
Weight	Unit: 0.65 lbs. / Shipping 1.50 lbs.	Unit: 0.65 lbs. / Shipping 1.50 lbs.
Housing	Metal IP30	Metal IP30
Mounting	DIN-Rail & Wall Mounting included	DIN-Rail & Wall Mounting included
ENVIRONMENTAL LIMITS		
Operating Temperature	STD: 0 to 55°C	STD: 0 to 55°C